

Single/Multicarrier Block Transmission Systems Optimal Pilot Design for Channel Estimation

Mahima Raikhere¹ and Prof. Aparna Gupta²

M.Tech. Scholar, Department of Electronics and Communication Engineering, LNCTS, Bhopal¹, M.P.

Department of Electronics and Communication Engineering, LNCTS, Bhopal², M.P. India

Abstract-The sensor nodes communicate together by wireless techniques, and these communication techniques are handled for channel estimation pilot sequence is design in such way that frequency selection is single carrier SC and multi-carrier MC block transmission systems. The Bayesian Cramer Rao bound BCRB is minimized by the channel estimation with training design for MSE. which also gives us the knowledge about channel combined with receiver noise covariance and which is subject to total transmit power constraint. The optimal pilot sequence which is applicable for 4 block transmission systems that is single carrier - zero padding, multicarrier -zero padding, single carrier - cyclic prefix, multi-carrier - cyclic prefix system which is driving from propose approaches. The framework proposed, and drive results will be general with the wide applicability. In the terms of MSE and BER both the conventional pilot design is present less result in comparison to the simulation results will good of the proposed pilot design approach.

1. Introduction

In the transmission systems the symbols are transmit continuously to transmitter to receiver in the wireless channel that are introduced very high interference due to large time spent for spread of communication channel. Overcome that difficulty many schemes are allow to verify at this places symbols are transmitted in block because they give us inter block interference free communication with guard intervals like ZP or CP. The method which give us low complexity for implementation and good quality and conditions of being strong against frequency selectivity of the wireless system is OFDM, OFDM is widely uses in CP based MC block transmission technique and it gain most of popularity. But many time OFDM is tolerate from high peak-to-average-power ratio PAPR, at zero location of the channel frequency response which have symbol recovery is unreliable and carrier frequency offset are quick to detect and respond to slight changes. In (2), (3), (4) and (5) used different single carrier block transmission technique to combat problems of OFDM which are PAPR for quality discovery, they work with ZP or CP for single carrier block transmission. To short coming of OFDM the ZP is definitely reliable symbol recovery regardless of channel zero location. (2), (5), (6) are work in detailed with the study of both transmission SC and MC, they study a comparatively of

CP and ZP systems. With comparison the other guided media the wireless channels are highly dynamic in nature due to this nature in wireless system essential thing of reliable decoding is channel estimation. If at the receiver end the knowledge for the diversity gain and data rate will be guaranteed increase in communication system, it is only by CSI. The Blind schemes and Training schemes are two categories of the channel estimation approaches in the training schemes a pilot sequence is known that is used for channel estimation based on received signals with respect to transmitted signals and which relies on special quality of transmitted sequence and static information of the channel. The blind scheme is tolerant from a high computer complexity, their higher bandwidth efficiency without being affected give disability to getting the channel fully estimation only up to remaining not definite factor. But preparing based technique that have less computer robustness (8),(9) increases their performance with a consideration of training based scheme. For achieving the maximum performance benefits from this scheme is critical for optimal pilot design. For MIMO-OFDM systems and for OFDM specifically both works are shown architecture of pilot which is optimal sequence. This paper is not uses any work in literature for unified pilot design framework for normal basic unit based wireless transmission system.

2. The System Model





Fig. 2. Comparison of BER performance of the proposed optimal pilot design scheme with the conventional random pilot scheme for SC-ZP design scheme with the conventional random pilot scheme and BCRB wireless systems.

Different basic unit of basic transmission like

- SC-ZP system
- MC-ZP system
- SC-CP system
- MC-CP system

3. Related Works

Various researchers have contributed in the area of the Single/Multicarrier Block

Transmission System Optimal Pilot Design for Channel Estimation—

1. In the full duplex MIMO system proposed the partial pilot transmission method for decreasing the pilot overhead for the signal interference (SI) channel estimation. The selection of antenna for pilot transmission to increase the partial pilot transmission method consider the recent channel state information and left for their future work the required M_p for optimization. The MSE and uplink achievable rate of the partial pilot transmission method analyzed by them. For getting great ergodic uplink achievement rates the partial transmission method is used, and partial pilot transmission methodology is giving high rate of MSE as compared to the full pilot transmission methodology. By **Kyungsik Min**, **Sangjoon Park**†, and **Sooyong Choi**◆
2. That review, they work on the ICFO estimation difficulty of the DLMT channel system which is all tolerate time railing channel fading. In starting they designed dual-CAZAC preamble architecture of DLMT channel system and then they use to design dual-CAZAC by WCAFBased ICFO estimation algorithm are proposed. Outperforms traditional ICFO estimator on the correct estimation probability performance. By **Wei Xie**, **Kui Xu**, **Youyun Xu**, **Dongmei Zhang**
3. This paper addressed optimal pilot in the ML location for system which is multicarrier for channel estimation and MMSE criteria. The optimality conditions for a general channel correlation matrix are given and further easy for taps of channel which are uncorrelated. The equal spaced pilot structure is a situation commonly general is allowing in the family of optimal addresses. By **François Rottenberg**◆†, **François Horlin**†, **Eleftherios Kofidis**‡ and **Jérôme Louveaux**◆
4. Channel estimation performance depends greatly on the statistical properties of the interference environment. It has been shown by many examples which are optimized to making an essential scheme versed mainly worked ES PP and few times one resultant for DSA application. For pilot design highly efficient channel used for optimizations, they necessarily use the great count of subcarrier of pilot. By **Eugene Golovins** and **Neco Ventura**
5. In this paper investigated the analytical impact of PC with several pilot based

channel estimation algorithm, which includes LS, MMSE classical algorithm and their proposed H-inf algorithm in multi cell MU-MIMO system. This considers imperfect channel estimation, multicarrier and MPC under realistic system model. To increase only a few amount of the number of OFDM subcarrier the optimal MMSE is most resistant to PC with high complexity. MMSE gives achievement to the PC subcarriers. For leading to better supraportion to PC than LS, DFT and ML the MMSE have same performance as H-inf algorithm. By **Peng Xu, Jiangzhou Wang, Senior**

Member, IEEE, Jinkuan Wang, Member, IEEE, Feng Qi.

6. The distinctive feature of the developed CRMIMO-MCPP solution is the concurrent optimality property from both channel estimation and receiver complexity standpoint. Simulation examples have shown the advantages of the MMSE-type channel estimation algorithms specifically for the opportunistic pilot positioning in the band, which is necessitated by the CR channel limitations. The RMMSE scheme is particularly attractive from the practical standpoint as its design does not rely on the a priori known channel response covariance unlike the optimal MMSE counterpart. By **Eugene Golovins and Neco Ventura**

4. Proposed Methodology

A. Pilot design

- By increasing or decreasing a frame length and a symbolize of our wireless system. I will try to decrease to BER and MSE of channel.

B. Modulation techniques

- I will use BPSK and PAM, if error are not decrease then I use m-PSK or m-QAM, where $m=2,4,8,16,32\dots$

C. MIMO (spatial diversity)

- I will use multiple input and multiple output wireless system 2×2 , 4×2 , 4×4 , 2×4 , 4×4 , 8×8 and try to reduce the BER and MSE.

D. Digital filters

- I will use window-based filters like 1-d filters.
- 1-d filters are FIR and IIR.
- Pulse shaping filters.

E. Detection methods

- I will try to reduce BER and MSE by using different detection method like ZF or MMSE (minimum mean square error)

5. Conclusions and Future Work

The paper is proposing interestingly new approaches for making optimal pilot sequence based on the proposed methodology for wireless system which is based on block transmission. For ZF or CP and single carrier and multicarrier system use the general proposed approaches. In comparison to suboptimal pilot sequence is the result of the simulation which gives performance increment of MSE and BER.

For better communication in wireless channels which medium is random nature there noise, distortion, scattering, fading, interference is introduced by channel estimation BER and MSE will decrease definitely.

6. References

1. In Full-Duplex MIMO Systems for Self-Interference Partial Pilot Transmission for Channel Estimation, Kyungsik Min and Sooyong Choi, School of Electrical and Electronic Engineering, Yonsei University.
2. M. Yee, M. Sandell, and Y. Sun, "Comparison study of single carrier and multi-carrier modulation using iterative based receiver for MIMO system," in IEEE Vehicular Technology Conference, 2004, pp. 1275–1279.
3. for Dynamic Lattice Multicarrier Transmission System Integer Frequency Offset Estimation over Time-Varying Rayleigh Fading Channel. Kui Xu, Wei Xie.
4. B. Muquet, Z. Wang, G. B. Giannakis, M. de Courville, and P. Duhamel, "Cyclic prefixing or zero padding for wireless multicarrier transmissions?" IEEE Transactions on Communications, vol. 50, no. 12, pp. 2136–2148, 2002.
5. DOI 10.1109/TVT.2014.2322654, IEEE Transactions on Vehicular Technology IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. XX, NO. XX, XX 2014 1 Analysis and Design of Channel Estimation in Multi-cell Multi-user MIMO OFDM Systems Peng Xu, Jiangzhou Wang, Senior Member. Optimised Pilot Pattern for Dynamic Spectrum Access Multicarrier Systems. Eugene Golovins and Neco Ventura Department of Electrical engineering
6. "Interference suppression for multicarrier and single-carrier block transmission systems and blind- channel estimation," IEEE Transactions on Vehicular Technology, vol. 57, no. 5, pp. 2779–2791, 2008. K. Amle and H. Li.
7. "With multiple transmit antennas simplified channel estimation for OFDM systems," IEEE Transactions on Wireless Communications, vol. 1, no. 1, pp. 67–75, 2002. Y. Li.
8. "In a mobile OFDM system, Pilot tone selection for channel estimation," IEEE Transactions on Consumer Electronics, vol. 44, no. 3, pp. 1122–1128, 1998. R. Negi and J. Cioffi.
9. "A fourth-generation MIMO- OFDM broadband wireless system: field trial results, design and performance" IEEE Communications Magazine, vol. 40, no. 9, pp. 143–

149,2002.H.Samath,S.Talwar,J.Tellado,V.Erceg,andA.aulraj.

10. Modulation theory, detection and estimation, optimum array processing. John Wiley & Sons,2004. H.L. Van Trees.